© Illumino Ignis Ltd. 2026. All Rights Reserved

Illumino Ignis Ltd™
LIGHTING & FIRE DESIGN, SUPPLY & SUPPORT

Detector Mounting Base

Addressable - Devices

Part No. UB-6-EV

www.illuminoignis.co.uk


Product Details

The Nittan UV-6-EV is a universal mounting base designed to be compatible with the entire range of Evolution detectors to provide a reliable and secure fixing point for each of your selected detectors.



Technical Specifications

Operating Voltage	10 to 38V d.c
Operating Temperature	– 10°C to + 55°C
Storage Temperature	– 25°C to + 70°C
Relative Humidity	≤ RH95% non-condensing
Material	ABS
Dimensions	Ø104.50mm x 15.00mm
Mass	52g
EMC Conformance	EMC conformance to BSEN50130-4
CE Conformity	Yes
Standards / Certification	Complies with EN54-5, 7



Conventional Terminations

1 = –VE In
6 = –VE Out
3 = +VE In/Out
5 = RIL –VE 2mA
4 = Screen

Addressable Terminations

1 = +VE In/Out
6 = –VE In/Out
3 = RIL –VE 2mA
4 = Screen
2 = AUX –VE

Addressable detector with Isolator Terminations

1 = +VE In/Out
6 = –VE In
5 = –VE Out
(SCI Only)
3 = RIL –VE 2mA
4 = Screen
2 = AUX –VE

0203 00 44 855
sales@illuminoignis.co.uk
illuminoignis.co.uk

Illumino Ignis Ltd, Ignis House,
Imperial Way, Eagle Business Park,
Yaxley, Cambridgeshire, PE7 3GP