


Illumino Ignis Ltd

LIGHTING & FIRE DESIGN, SUPPLY & SUPPORT

24V 5A Relay On A Plate


Accessories – Ancillary

Part No. BF376

www.illuminoignis.co.uk

Key Features

- A general purpose, double-pole, polarised 24V 5A relay designed for use in 24V fire alarm systems.
- Incorporates a high intensity LED which illuminates red when the relay is active.
- Can be connected to a suitable control panel relay output or a standard polarised fire alarm sounder circuit to operate door retaining magnets, rollershutter doors, etc.
- Can be mounted on 25mm flush or surface mount back boxes.



Technical Specifications

Activation current	Typically 30mA @ 24VDC.
Indicators	Red Relay Activated LED.
Connections	+V; -V (Supply); NC; C; NO (SW1 & SW2). Contact rating @ 24VDC is 5A (resistive) 2A (inductive); Contact rating @ 240VAC is 5A (resistive) 2A (inductive)
Product dimensions (mm)	85 W x 85 H x D 27mm (Can be mounted on a standard UK 25mm single gang flush or surface back box).
Construction & finish	White PVC plate; Light grey label; Silver nickel contacts
IP Rating	IP40.
Weight	78g
Operating conditions/temperature	-10°C to +60°C.