



Manually Addressed Module

Addressable – Devices

Part No. VALKYRIE-AS

www.illuminoignis.co.uk

Product Details

The VALKYRIE AS is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, VALKYRIE AS can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (10 mA in alarm) and must be included in loop load calculations.



Technical Specifications

Supply Voltage	Loop Powered – 20V to 30V DC
Loop Current – Quiescent	550 uA max. with isolator
Loop Current – Sounder/Beacon Active	10 mA – 280 mW @ 28V DC included isolator
Maximum Sounder Output	100 dB (@ 1 meter – 30V DC)
Light Flash Rate	0,92 Hz
Cable Size	0.5-2.5 mm ²
Reset/Start-Up Times	20 seconds max
Protection Category	Type A – Indoor Use / Rating IP21C
Colour / Case Material	Red or White / ABS and PC
Operation Temperature	-10°C to 55°C
Max. Humidity	95% RH Non-Condensing
Dimensions	110 (D) x 85 (H) mm included base
Weight	254g inc. base & 304g inc. packaging

For EN54-13 compliance, please check the control panel manual specifications.