



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name	Solo Smoke Detector Tester
Trade Name	Solo A5-XXX (XXX denotes customer variant)
CAS No.	Mixture
EINECS No.	Mixture
REACH Registration No.	None assigned.
UFI	S5DP-5214-600G-G451

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Smoke simulation
Uses Advised Against	None known

1.3 Only representative of a non-Community manufacturer

Company Identification	Shift-Consult Hubert Scherzinger, 79108 Freiburg, Germany
Telephone	+49 7665 81 21 74
Manufacturer	
Company Identification	Detectortesters (No Climb Products Ltd), Edison House, 163 Dixons Hill Road Welham Green, Hertfordshire. AL9 7JE, United Kingdom
Telephone	+44 (0) 1707 282760
Fax	+44 (0) 1707 282777
E-Mail (competent person)	SDS@detectortesters.com

1.4 Emergency telephone number

Emergency Phone No.	+44 (0) 1707 282760
Mon-Thur (8:30-17:00) Fri (8:30-15:00)	





Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008 (CLP)	Aerosol 1; Extremely flammable aerosol. Pressurised container: May burst if heated.
--	--

2.2 Label elements

Hazard Pictogram(s)	According to Regulation (EC) No. 1272/2008 (CLP)  GHS02
Signal Word(s)	Danger.
Hazard Statement(s) EINECS No.	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Precautionary Statement(s)	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Pressurised container – Do not pierce or burn, even after use. P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

2.3 Other hazards

None

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol.

3.2 Substances

EC Classification No. 1272/2008

Hazardous Ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No	Hazard Pictogram(s) and Hazard Statement(s)
Butane	50-100	106-97-8	203-448-7	01-2119474691-32	GHS02, Flam. Gas 1; H220, GHS04, Press. Gas: Liquefied gas; H280
Propane	10-25	74-98-6	200-827-9	01-2119486944-21	GHS02, Flam. Gas 1; H220, GHS04, Press. Gas: Liquefied gas; H280
Ethanol	0-5	64-17-5	200-578-6	01-2119457610-43	GHS02, Flam. Liq. 2; H225; Eye Irrit. 2, H319



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

3.3 Additional Information

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures



Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin Contact	Wash skin with water
Eye Contact	Flush eyes with water for at least 15 minutes while holding eyelids open
Ingestion	Unlikely route of exposure

4.2 Most important symptoms and effects, both acute and delayed

None anticipated

4.3 Indication of any immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Pressurised container: May burst if heated.

5.1 Extinguishing media

Suitable Extinguishing media	Extinguish with carbon dioxide, dry chemical, foam or waterspray.
Unsuitable extinguishing media	Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Heating may cause pressure rise with risk of bursting

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions

SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Wear suitable gloves and eye/face protection.

6.2 Environmental precautions

Do not release large quantities into the surface water or into drains



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

6.3 Methods and material for containment and cleaning up

Collect mechanically and dispose of according to Section 13.

Absorb spillage in earth or sand. Transfer to a lidded container for disposal or recovery.

Containers must not be punctured or destroyed by burning, even when empty.

6.4 Reference to other sections

See Also Section 8 and 13

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking. Provide adequate ventilation. Do not eat, drink or smoke during work.

Wash hands thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Observe official regulations on storing packagings with pressurised containers

Storage temperature	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 deg C.
Storage life	Considered stable under normal conditions
Incompatible materials	None anticipated

7.3 Specific end use(s)

Smoke simulation

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Butane	106-97-8	600	1450	750	1810	WEL
Ethanol	64-17-5	1000	1920	–	–	WEL

WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit value

Not established.

8.1.3 PNECs and DNELs

Not established.



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

8.2 Exposure controls

Provide adequate ventilation.

8.2.1 Appropriate engineering controls

8.2.2 Personal protection equipment

Eye/ face protection 	If eye contact is likely: Wear protective eyewear (goggles, face shield, or safety glasses)
Skin protection (Hand protection/ Other) 	Wear suitable gloves if prolonged skin contact is likely. Gloves : Nitrile rubber
Respiratory protection 	No personal respiratory protective equipment normally required. Handling of larger amounts: In case of insufficient ventilation, wear suitable respiratory equipment. A suitable mask with filter type A (EN14387 or EN405) may be appropriate.
Thermal hazards	Not applicable.

8.2.3 Environmental Exposure Controls

Do not release large quantities into the surface water or into drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Aerosol.	Density	0.58 g/cm ³ @20 °C
Colour.	Colourless.	Vapour density	Not determined
Odour	Characteristic	Relative density	Not determined
Odour Threshold (ppm)	Not determined.	Solubility(ies)	Immiscible with water
pH (Value)	Not determined.	Partition Coefficient (n-Octanol/water)	Not determined.
Melting Point (°C)/ Freezing Point (°C)	Not determined.	Ignition temperature	365°C
Boiling point/ boiling range (°C)	-44 °C	Auto Ignition Point (°C)	Product is not selfigniting
Flash Point (°C)	Not applicable	Decomposition Temperature (°C)	Not determined.
Evaporation rate	Not applicable	Kinematic Viscosity/Viscosity (mPa. s)	Not determined.
Flammability (solid, gas)	Extremely flammable	Explosive properties	Not explosive.
Upper/lower flammability or explosive limit	Explosive Limit Ranges: 1.5-10.9 Vol-%	Oxidising properties	Not oxidising.
Vapour pressure	3.8 bar @20 °C		



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

9.2 Other information

Organic solvents – Content	98.9%
----------------------------	-------

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Stable under normal conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Heat and direct sunlight

10.5 Incompatible materials

None anticipated.

10.6 Hazardous decomposition product(s)

No hazardous decomposition products known.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Low acute toxicity.
Hazard label(s)	Non-irritant
Serious eye damage/irritation	Not classified.
Respiratory or skin sensitization	It is not a skin sensitiser.
Germ cell mutagenicity	There is no evidence of mutagenic potential.
Carcinogenicity	No evidence of carcinogenicity.
Reproductive toxicity	None anticipated.
STOT – single exposure	Not classified
STOT – repeated exposure	Not classified
Aspiration hazard	None anticipated.

11.2 Other information

None.



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Low toxicity to aquatic organisms.

12.2 Persistence and degradability

The product is readily biodegradable. Unlikely to persist

12.3 Bioaccumulative potential

The product has no potential for bioaccumulation.

12.4 Mobility in soil

Immiscible with water. The product is predicted to have low mobility in soil.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB

12.6 Other adverse effects

None.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Recycle only completely emptied packaging. Containers must not be punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an approved waste disposal facility. Do NOT landfill.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation. EAL 7055 Aerosol spray can

SECTION 14: TRANSPORT INFORMATION

14.1 UN number ADR Classification Code IMDG, IATA Label

UN 1950

14.2 UN proper shipping name

ADR Group	1950 AEROSOLS
IMDG	AEROSOLS
IATA Label	AEROSOLS, Flammable



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

14.3 Transport hazard class(es) ADR Group

Class /Classification	2 5F Gases
LabelADR-RID Labels	2.1
IMDG, IATA Label	
Class / Division	2.1
Label	2.1
Hazard label(s)	

14.4 Packing group

ADR Classification CodeIMDG, IATA Label	None.
---	-------

14.5 Environmental hazards Marine Pollutant

No

14.6 Special precautions for user – Warning: Gases

Kemler Code	-
IMDG EMS	F-D, S-U

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

14.8 Additional Information ADR Classification Code

Limited Quantity (LQ)

1L



ADR Transport Category
Tunnel Restriction Code

2

Not applicable in Limited Quantities

IMDG
Limited Quantity (LQ)

1L



IATA Label
Limited Quantity (LQ)

1L



UN Model Regulation

UN1950 , AEROSOLS, 2.1



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU regulations

Authorisations and/or Restrictions On Use	All chemicals are not listed
Candidate List of Substances of Very High Concern for Authorisation	All chemicals are not listed
REACH: ANNEX XVII restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles	All chemicals are not listed
REACH: ANNEX XIV list of substances subject to authorisation	All chemicals are not listed
Community Rolling Action Plan (CoRAP)	None known.

15.1.2 National regulations

Wassergefährdungsklasse (Germany)	WGK class 1
Ethanol	Class: NK Share in %: 50-100
Technical Instructions (air)	
VOC-CH	98.93%
VOC-EU	569.8g/l
Danish MAL Code	3-1

15.2 Chemical Safety Assessment

Not available.



Smoke Test Can, 250ml (Flammable)

Accessories – Servicing

Part No. SOLO-A5

www.illuminoignis.co.uk

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: header.

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
STOT	Specific Target Organ Toxicity
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	Persistent, Bioaccumulative and Toxic
VPvB	very Persistent and very Bioaccumulative
WGK	Wassergefährdungsklasse (Germany)
VOC	Volatile Organic Compounds
MAL Code	Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)
ADR	Accord européen relative au transport international des marchandises dangereuse par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG	International Maritime Code for Dangerous Goods
IATA	International Air Transport Association
Press. Gas	Gases under pressure
Flam. Gas 1	Flammable gas. Flammable gas Category 1

Hazard Statement(s)

H220	Extremely flammable gas
H225	Highly flammable liquid and vapour
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation

Disclaimers

The information is based on the best knowledge of No Climb Products Ltd. and its advisors and is given in good faith, but we cannot guarantee its accuracy, reliability or completeness and therefore disclaim any liability for loss or damage arising out of use of this data. Since conditions of use are outside the control of the Company and its advisors we disclaim any liability for loss or damage when the product is used for purposes other than it is intended.

Annex to the extended Safety Data Sheet (eSDS)

No information available.