© Illumino Ignis Ltd. 2026. All Rights Reserved

Illumino Ignis Ltd™
LIGHTING & FIRE DESIGN, SUPPLY & SUPPORT

SmartCell Fire Manual Call Point

Radio - Devices

Part No. SC-51-0100-0001-99

www.illuminoignis.co.uk

Product Details

The SmartCell Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Key Features

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism

Technical Specifications

General	Status indication	LED
	Wireless frequency	868 MHz
	Compatibility	SmartCell
Physical	Physical dimensions	92 x 97 x 47 mm (W x H x D)
	Net weight	0.2 kg
	Colour	Red
	Mounting type	Wall mount
	Batteries	2 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
Environmental	Operating temperature	-10 to +55°C
	Storage temperature	-10 to +55°C (without batteries)
	Relative humidity	95% noncondensing max.
	Environment	Indoor
Standards & regulation	Compliancy	CE
	Certification	CPR
	Standards	EN54-13 EN54-25

0203 00 44 855
sales@illuminoignis.co.uk
illuminoignis.co.uk

Illumino Ignis Ltd, Ignis House,
Imperial Way, Eagle Business Park,
Yaxley, Cambridgeshire, PE7 3GP