© Illumino Ignis Ltd. 2026. All Rights Reserved

Illumino Ignis Ltd™
LIGHTING & FIRE DESIGN, SUPPLY & SUPPORT

CFP Relay Output Card (Reset, Fault, Aux. & Remote & 8 Output Per Zone Relays)

Conventional - Panel

Part No. CFP763

www.illuminoignis.co.uk


Product Details

The C-TEC CFP763 Relay / Output Board is an expansion module designed to add additional relay and zone output functionality to C-TEC CFP fire alarm control panels.

When installed, the board provides four panel-controlled volt-free relay outputs for key system events including fault, reset, auxiliary and remote output, allowing the fire alarm panel to interface with other building systems.

The module also provides up to eight configurable zone outputs, enabling enhanced control and integration with external equipment such as remote indicators, building management systems or auxiliary signalling devices.

Designed for simple plug-and-play installation, the CFP763 connects directly to compatible CFP conventional fire alarm panels, providing a straightforward way to expand system functionality without complex wiring.



Key Features

- An optional system expansion device for use with CFP Standard 2-8 Zone Fire Panels or CFP AlarmSense 2-8 Zone Fire Panels.
- Provides four panel-controlled volt free relay outputs (reset, fault, aux. fire and remote) and eight output per zone relays.
- PCB mounts inside the CFP fire panel.
- Reset relay is active during the panel's reset cycle.
- Fault relay is active in any fault condition. This relay is failsafe and normally energised - if power is removed from the panel the relay will changeover to produce a fault signal.
- Aux. fire relay is active in an alarm condition provided all relevant delays have expired.
- Remote relay is active during any Alarm Condition provided all relevant delays have expired.
- Output per zone relays will changeover when the corresponding zone is in alarm (subject to certain conditions - for full details refer to the instructions, downloadable below).
- Outputs are NOT designed to switch mains voltages.

Technical Specifications

Product dimensions (mm)	82 W x 125 H x D 23mm
Weight	116g.
Properties	Single pole changeover contacts; Rated at 1A 50V; 50V Isolation between relays, contacts and CFP & relays; 27mA active relay coil current @ 27.6V supply.

0203 00 44 855
sales@illuminoignis.co.uk
illuminoignis.co.uk

Illumino Ignis Ltd, Ignis House,
Imperial Way, Eagle Business Park,
Yaxley, Cambridgeshire, PE7 3GP