



Solo 365 Smoke Detector Testor

Accessories – Servicing

Part No. SOLO 365-001

www.illuminoignis.co.uk

Product Details

Solo 365 is an exciting, new innovation for testing smoke detectors. It offers everything the industry expects from the popular Solo brand, pairing it with the very latest technology and wrapping it in a new modern slim-line design.

Key Features

- Auto-start' proximity sensor – faster testing, less smoke waste
- Auto-LED torch – allows simple testing of detectors in dark areas
- Slim-line design – easier access to detectors in confined spaces
- Clearing mode – eliminates re-alarms, increasing productivity
- Delayed start mode – for non-standard detectors and ASD systems

The detector friendly smoke, generated via non-pressurised capsules, is compatible with the widest range of detectors and offers improved performance at low temperatures. Solo 365 is 15% lighter than the traditional Solo dispenser – supporting easier movement around site and when testing.



Includes

- 1 x Solo 365 Head Unit
- 1 x Solo 370 Lithium Ion Battery Pack
- 1 x Solo 371 Smoke Generator
- 1 x Solo ES3 Smoke Cartridge
- 1 x Spare 1060 Charger & USB Lead

Technical Specifications

Operating features	• Colour coded LED user information. • Proximity sensor starts test. • Suitable for detectors up to 110mm diameter. • 5 seconds of stimulus, 5 seconds off repeat cycles.
Safety features	• Battery over current cut out. • Over temperature cut out. • 2 minutes maximum duration time-out. • Auto power off after 10 minutes.
Power source	Lithium Ion battery pack nominal 3.63V 9.5Wh, with USB charger connection
Battery charging time	~2 hours
Operating temperature range	+5°C to 45°C (+41°F to 113°F)
Operating humidity range	0 to 85% RH non-condensing


Illumino Ignis Ltd™

LIGHTING & FIRE DESIGN, SUPPLY & SUPPORT

Solo 365 Smoke Detector Testor

Accessories – Servicing

Part No. SOLO 365-001

www.illuminoignis.co.uk

Technical Specifications – Continued

Storage temperature range	-10°C to 50°C (+14°F to 122°F)
Storage humidity range	0 to 90% RH non-condensing (up to +35°C/95°F)
Weight (Including battery, generator & cartridge)	860g
Dimensions H (including handle) x W (widest) x D	420mm x 190mm x 110mm
Dimensions H (excluding handle) x W (widest) x D	295mm x 190mm x 110mm
Dimensions as above with cup in user position	260mm x 190mm x 150mm
Clear cup dimensions	150mm x 85mm
Outer carton dimensions H x W x D	130mm x 525mm x 230mm